

2.35 CFC-13(R13)

All equations for CFC-13(R13) are based on the Table from Thermophysical properties of refrigerants by Platzer *et al.*[1].

2.35.1 Temperature Scale

International practical temperature scale 1968 (IPTS-1968)

2.35.2 The Names of Substance, Library File and Single Shot Program

| | |
|---|--|
| Name of Substance: | CFC-13, R13, Refrigerant 13, Freon 13, Chlorotrifluoromethane |
| Library File for UNIX: | libjr13.a |
| Library File for DOS,Windows95/NT: | JR13.LIB |
| Single Shot Program for UNIX: | r13-ss |
| Single Shot Program for DOS,Windows95/NT: | R13-SS.EXE |

2.35.3 Important Constants and Others

| | |
|--------------------------|-------------------|
| Molecular Formula: | CClF ₃ |
| Relative Molecular Mass: | 104.470 |
| Gas Constant: | 79.5875 J/(kg·K) |

Critical Constants:

| | |
|---------------------------|--|
| Critical Pressure: | 3.8770×10 ⁶ Pa (38.770 bar) |
| Critical Temperature: | 301.88 K (28.73 °C) |
| Critical Specific Volume: | 1.7182×10 ⁻³ m ³ /kg |

Reference State:

At 0°C, 1.0000 kJ/(kg·K) and 200.00 kJ/kg are assigned to the specific entropy and the specific enthalpy of saturated liquid, respectively.

2.35.4 Formula

Equation of State:

The Bender equation of state (II-3-1) in reference [1], which is in a function from of $Z = Z(\rho, T)$. Here Z =compressibility, ρ =density and T =temperature.

Vapor Pressure:

Equation (20) in reference [1].

Properties at Vapor-Liquid Equilibrium:

saturated state: The Bender equation of state is utilized to obtaining saturated specific volume by the aid of Maxwell's criterion according to the author's recommendation. The Bender equation of state shows unreasonable behavior near the critical point. This temperature range is evaluated by $T_c \pm 1$ K. Therefore, in the temperature range and above the critical pressure, the values of u , h and s would include some uncertainty. Also, in the ranges of $p_{sat}(T_c - 1K) < p < p_{sat}(T_c + 1K)$ and $v'(T_c - 1K) < v < v''(T_c - 1K)$, the calculated values of p , v , T , c_p , c_v , isentropic exponent, Laplace coefficient, Prandtl number, velocity of sound and dryness fraction of wet vapor would have some uncertainty. Equations (2), (3), and (5) for specific enthalpy, specific entropy and isobaric specific heat, respectively. However, the sign of the last integration term in Equation (2) for u

$$u(T, \rho) = h_0 - RT_0 + \int_{T_0}^T (c_p^0 - R)dT + \int_0^\rho \left[T \left(\frac{\partial p}{\partial T} \right)_\rho - p \right] \frac{d\rho}{\rho^2}$$

has been corrected to

$$u(T, \rho) = h_0 - RT_0 + \int_{T_0}^T (c_p^0 - R)dT - \int_0^\rho \left[T \left(\frac{\partial p}{\partial T} \right)_\rho - p \right] \frac{d\rho}{\rho^2}.$$

Transport Properties:

Thermal conductivity and viscosity from reference [2].

The Other Properties:

Equation (3) in reference [3] for surface tension.

References

- [1] B.Platzer, A.Polt and G.Maurer, Thermophysical Properties of Refrigerants (1990), Springer-Verlag
- [2] Thermophysical Properties of Refrigerants(1976), 13 ASHRAE
- [3] K.Watanabe and M.Okada, Int. J. Thermophysics, 2-2(1981), p.163

Table II-2.35-1 CFC-13(R-13) Function

| No. | Name of Function | Function and Argument(s) | Range of Argument(s) |
|-----|------------------|---|--|
| 1 | AIPPT(P,T) | | |
| 94 | AJTPT(P,T) | | |
| 8A | AKPD(P) | | |
| 8B | AKPDD(P) | | |
| 82 | AKPT(P,T) | AKPT: Isentropic Exponent [-] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C] | $500 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $150 \leq T \leq 450$ [K] $5 \leq P \leq 500$ [bar] $-123.15 \leq T \leq 176.85$ [°C] |
| 8C | AKTD(T) | | |
| 8D | AKTDD(T) | | |
| 2 | ALAPP(P) | ALAPP: Laplace Coefficient [m] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] |
| 3 | ALAPT(T) | ALAPT: Laplace Coefficient [m] T*: Temperature [K], [°C] | $140 \leq T \leq 301.88$ [K] $-133.15 \leq T \leq 28.73$ [°C] |
| 4 | ALHP(P) | ALHP: Latent Heat of Vaporization [J/kg] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] |
| 5 | ALHT(T) | ALHT: Latent Heat of Vaporization [J/kg] T*: Temperature [K], [°C] | $144.63 \leq T \leq 301.88$ [K] $-128.52 \leq T \leq 28.73$ [°C] |
| 6 | ALMPD(P) | ALMPD: Thermal Conductivity of Saturated Liquid [W/(m·K)] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 1.8178 \times 10^6$ [Pa] $0.031 \leq P \leq 18.178$ [bar] |
| 7 | ALMPDD(P) | ALMPDD: Thermal Conductivity of Saturated Vapor [W/(m·K)] T*: Temperature [K], [°C] | $400.5 \times 10^3 \leq P \leq 2.225 \times 10^6$ [Pa] $4.005 \leq P \leq 22.25$ [bar] |
| 8 | ALMPT(P,T) | ALMPT: Thermal Conductivity at Ordinary Pressure [W/(m·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C] | P=Dummy $222 \leq T \leq 533$ [K] $-51.15 \leq T \leq 259.85$ [°C] |
| 9 | ALMTD(T) | ALMTD: Thermal Conductivity of Saturated Liquid [W/(m·K)] T*: Temperature [K], [°C] | $94 \leq T \leq 270$ [K] $-179.15 \leq T \leq -3.15$ [°C] |
| 10 | ALMTDD(T) | ALMTDD: Thermal Conductivity of Saturated Vapor [W/(m·K)] T*: Temperature [K], [°C] | $222 \leq T \leq 278$ [K] $-51.15 \leq T \leq 4.85$ [°C] |
| 11 | AMUPD(P) | AMUPD: Coefficient of Viscosity of Saturated Liquid [Pa·s] P*: Pressure [Pa], [bar] | $154.4 \times 10^3 \leq P \leq 3.7114 \times 10^6$ [Pa] $1.544 \leq P \leq 37.114$ [bar] |
| 12 | AMUPDD(P) | AMUPDD: Coefficient of Viscosity of Saturated Vapor [Pa·s] P*: Pressure [Pa], [bar] | $92.23 \times 10^3 \leq P \leq 2.9604 \times 10^6$ [Pa] $0.9223 \leq P \leq 29.604$ [bar] |
| 13 | AMUPT(P,T) | | |
| 14 | AMUTD(T) | AMUTD: Coefficient of Viscosity of Saturated Liquid [Pa·s] T*: Temperature [K], [°C] | $200 \leq T \leq 300$ [K] $-73.15 \leq T \leq 26.85$ [°C] |
| 15 | AMUTDD(T) | AMUTDD: Coefficient of Viscosity of Saturated Vapor [Pa·s] T*: Temperature [K], [°C] | $190 \leq T \leq 290$ [K] $-83.15 \leq T \leq 16.85$ [°C] |
| 92 | BPPT(P,T) | | |
| 90 | BSPT(P,T) | | |
| 91 | BTPT(P,T) | | |
| 93 | BVPT(P,T) | | |
| 16 | CPPD(P) | CPPD: Isobaric Specific Heat of Saturated Liquid [J/(kg·K)] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] |
| 17 | CPPDD(P) | CPPDD: Isobaric Specific Heat of Saturated Vapor [J/(kg·K)] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] |

Table II-2.35-1 CFC-13(R-13) Function (cont'd)

| No. | Name of Function | Function and Argument(s) | Range of Argument(s) |
|-----|------------------|--|---|
| 18 | CPPT(P,T) | CPPT: Isobaric Specific Heat [J/(kg·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C] | $500 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $150 \leq T \leq 450$ [K] $5 \leq P \leq 500$ [bar] $-123.15 \leq T \leq 176.85$ [°C] |
| 19 | CPTD(T) | CPTD: Isobaric Specific Heat of Saturated Liquid [J/(kg·K)] T*: Temperature [K], [°C] | $144.63 \leq T \leq 301.88$ [K] $-128.52 \leq T \leq 28.73$ [°C] |
| 20 | CPTDD(T) | CPTDD: Isobaric Specific Heat of Saturated Vapor [J/(kg·K)] T*: Temperature [K], [°C] | $144.63 \leq T \leq 301.88$ [K] $-128.52 \leq T \leq 28.73$ [°C] |
| 21 | CRP('A') | CRP: Critical Constants H: 'A'='H': 0.2596×10^6 [J/kg] Specific Enthalpy P*: 'A'='P': 3.877×10^6 [Pa], 38.77 [bar] Pressure S: 'A'='S': 1.197×10^3 [J/(kg·K)] Specific Entropy T*: 'A'='T': 301.88 [K], 28.73 [°C] Temperature V: 'A'='V': 1.718×10^{-3} [m ³ /kg] Specific Volume | one of 'H', 'P', 'S', 'T' and 'V' |
| 7A | CVPD(P) | | |
| 76 | CVPDD(P) | CVPDD: Isochoric Specific Heat of Saturated Vapor [J/(kg·K)] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] |
| 77 | CVPT(P,T) | CVPT: Isochoric Specific Heat [J/(kg·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C] | $500 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $150 \leq T \leq 450$ [K] $5 \leq P \leq 500$ [bar] $-123.15 \leq T \leq 176.85$ [°C] |
| 7B | CVTD(T) | | |
| 78 | CVTDD(T) | CVTDD: Isochoric Specific Heat of Saturated Vapor [J/(kg·K)] T*: Temperature [K], [°C] | $144.63 \leq T \leq 301.88$ [K] $-128.52 \leq T \leq 28.73$ [°C] |
| 2A | EPSPD(P) | | |
| 2B | EPSPDD(P) | | |
| 22 | EPSP(T) | | |
| 2C | EPSTD(T) | | |
| 2D | EPSTDD(T) | | |
| 89 | FC('A') | FC: Fundamental Constants M: 'A'='M': 104.47 Relative Molecular Mass R: 'A'='R': 79.588 [J/(kg·K)] Gas Constant | one of 'M' and 'R' |
| 9A | GAMPD(P) | | |
| 96 | GAMPDD(P) | | |
| 95 | GAMP(T) | | |
| 9B | GAMTD(T) | | |
| 97 | GAMTDD(T) | | |
| 23 | HPD(P) | HPD: Specific Enthalpy of Saturated Liquid [J/kg] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] |
| 24 | HPDD(P) | HPDD: Specific Enthalpy of Saturated Vapor [J/kg] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] |
| 71 | HPS(P,S) | HPS: Specific Enthalpy [J/kg] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)] | $500 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] SPT(P,150K) $\leq S \leq$ SPT(P,450K) [J/(kg·K)] $5 \leq P \leq 500$ [bar] SPT(P,-123.15°C) $\leq S \leq$ SPT(P,176.85°C) [J/(kg·K)] |

Table II-2.35-1 CFC-13(R-13) Function (cont'd)

| No. | Name of Function | Function and Argument(s) | Range of Argument(s) |
|-----|------------------|--|---|
| 25 | HPT(P,T) | HPT: Specific Enthalpy [J/kg] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C] | $500 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $150 \leq T \leq 450$ [K] $5 \leq P \leq 500$ [bar] $-123.15 \leq T \leq 176.85$ [°C] |
| 26 | HPX(P,X) | HPX: Specific Enthalpy of Mixture [J/kg] P*: Pressure [Pa], [bar] X: Dryness Fraction [-] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] $0 \leq X \leq 1.0$ [-] |
| 27 | HTD(T) | HTD: Specific Enthalpy of Saturated Liquid [J/kg] T*: Temperature [K], [°C] | $144.63 \leq T \leq 301.88$ [K] $-128.52 \leq T \leq 28.73$ [°C] |
| 28 | HTDD(T) | HTDD: Specific Enthalpy of Saturated Vapor [J/kg] T*: Temperature [K], [°C] | $144.63 \leq T \leq 301.88$ [K] $-128.52 \leq T \leq 28.73$ [°C] |
| 29 | HTX(T,X) | HTX: Specific Enthalpy of Mixture [J/kg] T*: Temperature [K], [°C] X: Dryness Fraction [-] | $144.63 \leq T \leq 301.88$ [K] $-128.52 \leq T \leq 28.73$ [°C] $0 \leq X \leq 1.0$ [-] |
| 84 | IDENTF('A') | IDENTF: CHARACTER TYPE FUNCTION for Identification of Substance (Length 20) C: 'A'='C': 'CCLF3' Molecular Formula S: 'A'='S': 'CFC-13(R-13)' Name of Substance V: 'A'='V': '10.1' Version Number | one of 'C', 'S' and 'V' |
| 66 | PLDT(T) | | |
| 68 | PMLT(T) | | |
| 85 | PRPD(P) | PRPD: Prandtl Number of Saturated Liquid [-] P*: Pressure [Pa], [bar] | $154.4 \times 10^3 \leq P \leq 1.8178 \times 10^6$ [Pa] $1.544 \leq P \leq 18.178$ [bar] |
| 86 | PRPDD(P) | PRPDD: Prandtl Number of Saturated Vapor [-] P*: Pressure [Pa], [bar] | $400.5 \times 10^3 \leq P \leq 2.225 \times 10^6$ [Pa] $4.005 \leq P \leq 22.25$ [bar] |
| 81 | PRPT(P,T) | | |
| 87 | PRTD(T) | PRTD: Prandtl Number of Saturated Liquid [-] T*: Temperature [K], [°C] | $200 \leq T \leq 270$ [K] $-73.15 \leq T \leq -3.15$ [°C] |
| 88 | PRTDD(T) | PRTDD: Prandtl Number of Saturated Vapor [-] T*: Temperature [K], [°C] | $222 \leq T \leq 278$ [K] $-51.15 \leq T \leq 4.85$ [°C] |
| 99 | PSBT(T) | | |
| 30 | PST(T) | PST*: Saturation Pressure [Pa], [bar] T*: Temperature [K], [°C] | $150 \leq T \leq 301.88$ [K] $-123.15 \leq T \leq 28.73$ [°C] |
| 72 | PSTD(T) | | |
| 73 | PSTDD(T) | | |
| 31 | SIGP(P) | SIGP: Surface Tension [N/m] P*: Pressure [Pa], [bar] | $PST(150K) \leq P \leq 3.877 \times 10^6$ [Pa] ($\sim 5.25 \times 10^3$) $PST(-123.15 \text{ °C}) \leq P \leq 38.77$ [bar] (~ 0.0525) |
| 32 | SIGT(T) | SIGT: Surface Tension [N/m] T*: Temperature [K], [°C] | $150 \leq T \leq 301.88$ [K] $-123.15 \leq T \leq 28.73$ [°C] |
| 33 | SPD(P) | SPD: Specific Entropy of Saturated Liquid [J/(kg·K)] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] |
| 34 | SPDD(P) | SPDD: Specific Entropy of Saturated Vapor [J/(kg·K)] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] |
| 35 | SPT(P,T) | SPT: Specific Entropy [J/(kg·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C] | $500 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $150 \leq T \leq 450$ [K] $5 \leq P \leq 500$ [bar] $-123.15 \leq T \leq 176.85$ [°C] |
| 36 | SPX(P,X) | SPX: Specific Entropy of Mixture [J/(kg·K)] P*: Pressure [Pa], [bar] X: Dryness Fraction [-] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] $0 \leq X \leq 1.0$ [-] |

Table II-2.35-1 CFC-13(R-13) Function (cont'd)

| No. | Name of Function | Function and Argument(s) | Range of Argument(s) |
|-----|------------------|---|---|
| 37 | STD(T) | STD: Specific Entropy of Saturated Liquid [J/(kg·K)] T*: Temperature [K], [°C] | 144.63 ≤ T ≤ 301.88 [K] -128.52 ≤ T ≤ 28.73 [°C] |
| 38 | STDD(T) | STDD: Specific Entropy of Saturated Vapor [J/(kg·K)] T*: Temperature [K], [°C] | 144.63 ≤ T ≤ 301.88 [K] -128.52 ≤ T ≤ 28.73 [°C] |
| 39 | STX(T,X) | STX: Specific Entropy of Mixture [J/(kg·K)] T*: Temperature [K], [°C] X: Dryness Fraction [-] | 144.63 ≤ T ≤ 301.88 [K] -128.52 ≤ T ≤ 28.73 [°C] 0 ≤ X ≤ 1.0 [-] |
| 67 | TLDP(P) | | |
| 69 | TMLP(P) | | |
| 64 | TPH(P,H) | TPH*: Temperature [K], [°C] P*: Pressure [Pa], [bar] H: Specific Enthalpy [J/kg] | 500 × 10 ³ ≤ P ≤ 50 × 10 ⁶ [Pa] HPT(P,150K) ≤ H ≤ HPT(P,450K) [J/kg] 5 ≤ P ≤ 500 [bar] HPT(P,-123.15°C) ≤ H ≤ HPT(P,176.85°C) [J/kg] |
| 6H | TPH2(P,H) | | |
| 65 | TPS(P,S) | TPS*: Temperature [K], [°C] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)] | 500 × 10 ³ ≤ P ≤ 50 × 10 ⁶ [Pa] SPT(P,150K) ≤ S ≤ SPT(P,450K) [J/(kg·K)] 5 ≤ P ≤ 500 [bar] SPT(P,-123.15°C) ≤ S ≤ SPT(P,176.85°C) [J/(kg·K)] |
| 6S | TPS2(P,S) | | |
| 98 | TPSEUP(P) | | |
| 70 | TPV(P,V) | TPV*: Temperature [K], [°C] P*: Pressure [Pa], [bar] V: Specific Volume [m ³ /kg] | 500 × 10 ³ ≤ P ≤ 50 × 10 ⁶ [Pa] VPT(P,210K) ≤ V ≤ VPT(P,450K) [m ³ /kg] 5 ≤ P ≤ 500 [bar] VPT(P,-123.15°C) ≤ V ≤ VPT(P,176.85°C) [m ³ /kg] |
| 41 | TRPL('A') | | |
| 100 | TSBP(P) | | |
| 40 | TSP(P) | TSP*: Saturation Temperature [K], [°C] P*: Pressure [Pa], [bar] | 3.1 × 10 ³ ≤ P ≤ 3.877 × 10 ⁶ [Pa] 0.031 ≤ P ≤ 38.77 [bar] |
| 74 | TSPD(P) | | |
| 75 | TSPDD(P) | | |
| 42 | UPD(P) | UPD: Specific Internal Energy of Saturated Liquid [J/kg] P*: Pressure [Pa], [bar] | 3.1 × 10 ³ ≤ P ≤ 3.877 × 10 ⁶ [Pa] 0.031 ≤ P ≤ 38.77 [bar] |
| 43 | UPDD(P) | UPDD: Specific Internal Energy of Saturated Vapor [J/kg] P*: Pressure [Pa], [bar] | 3.1 × 10 ³ ≤ P ≤ 3.877 × 10 ⁶ [Pa] 0.031 ≤ P ≤ 38.77 [bar] |
| 79 | UPS(P,S) | UPS: Specific Internal Energy [J/kg] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)] | 500 × 10 ³ ≤ P ≤ 50 × 10 ⁶ [Pa] SPT(P,150K) ≤ S ≤ SPT(P,450K) [J/(kg·K)] 5 ≤ P ≤ 500 [bar] SPT(P,-123.15°C) ≤ S ≤ SPT(P,176.85°C) [J/(kg·K)] |
| 44 | UPT(P,T) | UPT: Specific Internal [J/kg] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C] | 500 × 10 ³ ≤ P ≤ 50 × 10 ⁶ [Pa] 150 ≤ T ≤ 450 [K] 5 ≤ P ≤ 500 [bar] -123.15 ≤ T ≤ 176.85 [°C] |

Table II-2.35-1 CFC-13(R-13) Function (cont'd)

| No. | Name of Function | Function and Argument(s) | Range of Argument(s) |
|-----|------------------|--|---|
| 45 | UPX(P,X) | UPX: Specific Internal Energy of Mixture [J/kg] P*: Pressure [Pa], [bar] X: Dryness Fraction [-] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] $0 \leq X \leq 1.0$ [-] |
| 46 | UTD(T) | UTD: Specific Internal Energy of Saturated Liquid [J/kg] T*: Temperature [K], [°C] | $150 \leq T \leq 301.88$ [K] $-123.15 \leq T \leq 28.73$ [°C] |
| 47 | UTDD(T) | UTDD: Specific Internal Energy of Saturated Vapor [J/kg] T*: Temperature [K], [°C] | $150 \leq T \leq 301.88$ [K] $-123.15 \leq T \leq 28.73$ [°C] |
| 48 | UTX(T,X) | UTX: Specific Internal Energy of Mixture [J/kg] T*: Temperature [K], [°C] X: Dryness Fraction [-] | $144.63 \leq T \leq 301.88$ [K] $-128.52 \leq T \leq 28.73$ [°C] $0 \leq X \leq 1.0$ [-] |
| 49 | VPD(P) | VPD: Specific Volume of Saturated Liquid [m ³ /kg] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] |
| 50 | VPDD(P) | VPDD: Specific Volume of Saturated Vapor [m ³ /kg] P*: Pressure [Pa], [bar] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] |
| 80 | VPS(P,S) | VPS: Specific Volume [m ³ /kg] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)] | $500 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] SPT(P,150K) ≤ S ≤ SPT(P,450K) [J/(kg·K)] $5 \leq P \leq 500$ [bar] SPT(P,-123.15°C) ≤ S ≤ SPT(P,176.85°C) [J/(kg·K)] |
| 51 | VPT(P,T) | VPT: Specific Volume [m ³ /kg] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C] | $500 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $150 \leq T \leq 450$ [K] $5 \leq P \leq 500$ [bar] $-123.15 \leq T \leq 176.85$ [°C] |
| 52 | VPX(P,X) | VPX: Specific Volume of Mixture [m ³ /kg] P*: Pressure [Pa], [bar] X: Dryness Fraction [-] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] $0 \leq X \leq 1.0$ [-] |
| 53 | VTD(T) | VTD: Specific Volume of Saturated Liquid [m ³ /kg] T*: Temperature [K], [°C] | $144.63 \leq T \leq 301.88$ [K] $-128.52 \leq T \leq 28.73$ [°C] |
| 54 | VTDD(T) | VTDD: Specific Volume of Saturated Vapor [m ³ /kg] T*: Temperature [K], [°C] | $144.63 \leq T \leq 301.88$ [K] $-128.52 \leq T \leq 28.73$ [°C] |
| 55 | VTX(T,X) | VTX: Specific Volume of Mixture [m ³ /kg] T*: Temperature [K], [°C] X: Dryness Fraction [-] | $144.63 \leq T \leq 301.88$ [K] $-128.52 \leq T \leq 28.73$ [°C] $0 \leq X \leq 1.0$ [-] |
| 8E | WPD(P) | | |
| 8F | WPDD(P) | | |
| 83 | WPT(P,T) | WPT: Velocity of Sound [m/s] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C] | $500 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $150 \leq T \leq 450$ [K] $5 \leq P \leq 500$ [bar] $-123.15 \leq T \leq 176.85$ [°C] |
| 8G | WTD(T) | | |
| 8H | WTDD(T) | | |
| 56 | XPH(P,H) | XPH: Dryness Fraction [-] P*: Pressure [Pa], [bar] H: Specific Enthalpy of Mixture [J/kg] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] HPD(P) ≤ H ≤ HPDD(P) [J/kg] |
| 57 | XPS(P,S) | XPS: Dryness Fraction [-] P*: Pressure [Pa], [bar] S: Specific Entropy of Mixture [J/(kg·K)] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] SPD(P) ≤ S ≤ SPDD(P) [J/(kg·K)] |
| 58 | XPU(P,U) | XPU: Dryness Fraction [-] P*: Pressure [Pa], [bar] U: Specific Internal Energy of Mixture [J/kg] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] UPD(P) ≤ U ≤ UPDD(P) [J/kg] |
| 59 | XPV(P,V) | XPV: Dryness Fraction [-] P*: Pressure [Pa], [bar] V: Specific Volume of Mixture [m ³ /kg] | $3.1 \times 10^3 \leq P \leq 3.877 \times 10^6$ [Pa] $0.031 \leq P \leq 38.77$ [bar] VPD(P) ≤ V ≤ VPDD(P) [m ³ /kg] |

Table II-2.35-1 CFC-13(R-13) Function (cont'd)

| No. | Name of Function | Function and Argument(s) | Range of Argument(s) |
|-----|------------------|--|--|
| 60 | XTH(T,H) | XTH: Dryness Fraction [-] T*: Temperature [K], [°C] H: Specific Enthalpy of Mixture [J/kg] | $144.63 \leq T < 301.88$ [K] $-128.52 \leq T < 28.73$ [°C] $HTD(T) \leq H \leq HTDD(T)$ [J/kg] |
| 61 | XTS(T,S) | XTS: Dryness Fraction [-] T*: Temperature [K], [°C] S: Specific Entropy of Mixture [J/(kg·K)] | $144.63 \leq T < 301.88$ [K] $-128.52 \leq T < 28.73$ [°C] $STD(T) \leq S \leq STDD(T)$ [J/(kg·K)] |
| 62 | XTU(T,U) | XTU: Dryness Fraction [-] T*: Temperature [K], [°C] U: Specific Internal Energy of Mixture [J/kg] | $144.63 \leq T < 301.88$ [K] $-128.52 \leq T < 28.73$ [°C] $UTD(T) \leq U \leq UTDD(T)$ [J/kg] |
| 63 | XTV(T,V) | XTV: Dryness Fraction [-] T*: Temperature [K], [°C] V: Specific Volume of Mixture [m ³ /kg] | $144.63 \leq T < 301.88$ [K] $-128.52 \leq T < 28.73$ [°C] $VTD(T) \leq V \leq VTDD(T)$ [m ³ /kg] |