

2.31 FC-14(R14)

All equations for FC-14(R14) are based on the Table from Thermophysical properties of refrigerants by Platzer *et al.*[1].

2.31.1 Temperature Scale

International practical temperature scale 1968 (IPTS-1968)

2.31.2 The Names of Substance, Library File and Single Shot Program

Name of Substance:	FC-14, R14, Refrigerant 14, Freon 14, Carbontetrafluoride
Library File for UNIX:	libjr14.a
Library File for DOS,Windows95/NT:	JR14.LIB
Single Shot Program for UNIX:	r14-ss
Single Shot Program for DOS,Windows95/NT:	R14-SS.EXE

2.31.3 Important Constants and Others

Molecular Formula:	CF ₄
Relative Molecular Mass:	88.010
Gas Constant:	94.4723 J/(kg·K)

Critical Constants:

Critical Pressure:	3.7500×10 ⁶ Pa (37.500 bar)
Critical Temperature:	227.51 K (-45.64 °C)
Critical Specific Volume:	1.5982×10 ⁻³ m ³ /kg

Reference State:

At 0°C, 1.0000 kJ/(kg·K) and 200.00 kJ/kg are assigned to the specific entropy and the specific enthalpy of saturated liquid, respectively.

2.31.4 Formula

Equation of State:

The Bender equation of state (II-3-1) in reference [1], which is in a function from of $Z = Z(\rho, T)$. Here Z =compressibility, ρ =density and T =temperature.

Vapor Pressure:

Equation (20) in reference [1].

Properties at Vapor-Liquid Equilibrium:

saturated state: The Benderequation of state is utilized to obtaining saturated specific volume by the aid of Maxwell's criterion according to the author's recommendation. The Bender equation of state shows unreasonable behavior near the critical point. This temperature range is evaluated by $T_c \pm 1$ K. Therefore, in the temperature range and above the critical pressure, the values of u , h and s would include some uncertainty. Also, in the ranges of $p_{sat}(T_c - 1K) < p < p_{sat}(T_c + 1K)$ and $v'(T_c - 1K) < v < v''(T_c - 1K)$, the calculated values of p , v , T , c_p , c_v , isentropic exponent, Laplace coefficient, Prandtl number, velocity of sound and dryness fraction of wet vapor would have some uncertainty. Equations (2), (3), and (5) for specific enthalpy, specific entropy and isobaric specific heat, respectively. However, the sign of the last integration term in Equation (2) for u

$$u(T, \rho) = h_0 - RT_0 + \int_{T_0}^T (c_p^0 - R)dT + \int_0^\rho \left[T \left(\frac{\partial p}{\partial T} \right)_\rho - p \right] \frac{d\rho}{\rho^2}$$

has been corrected to

$$u(T, \rho) = h_0 - RT_0 + \int_{T_0}^T (c_p^0 - R)dT - \int_0^\rho \left[T \left(\frac{\partial p}{\partial T} \right)_\rho - p \right] \frac{d\rho}{\rho^2}.$$

However, the coefficients of the ideal gas state heat capacity equation (15) ($d_2 \sim d_5$) are revised by kind information from the authors. The correct values are the followings.

$$d_2 = 8.285805E - 6, \quad d_3 = 8.405900E - 6, \quad d_4 = -1.787524E - 8, \quad d_5 = 1.149856E - 11$$

Transport Properties:

Thermal conductivity from reference[2].

References

- [1] B.Platzer, A.Polt and G.Maurer, Thermophysical Properties of Refrigerants (1990), Springer-Verlag
- [2] Thermophysical Properties of Refrigerants(1976), 22 ASHRAE

Table II-2.31-1 FC-14(R-14) Function

No.	Name of Function	Function and Argument(s)	Range of Argument(s)
1	AIPPT(P,T)		
94	AJTPT(P,T)		
8A	AKPD(P)		
8B	AKPDD(P)		
82	AKPT(P,T)	AKPT: Isentropic Exponent [-] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$600 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $110 \leq T \leq 620$ [K] $6 \leq P \leq 500$ [bar] $-163.15 \leq T \leq 346.85$ [°C]
8C	AKTD(T)		
8D	AKTDD(T)		
2	ALAPP(P)		
3	ALAPT(T)		
4	ALHP(P)	ALHP: Latent Heat of Vaporization [J/kg] P*: Pressure [Pa], [bar]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar]
5	ALHT(T)	ALHT: Latent Heat of Vaporization [J/kg] T*: Temperature [K], [°C]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C]
6	ALMPD(P)	ALMPD: Thermal Conductivity of Saturated Liquid [W/(m·K)] P*: Pressure [Pa], [bar]	$69.7 \times 10^3 \leq P \leq 2.1863 \times 10^6$ [Pa] $0.697 \leq P \leq 21.863$ [bar]
7	ALMPDD(P)	ALMPDD: Thermal Conductivity of Saturated Vapor [W/(m·K)] T*: Temperature [K], [°C]	$93.67 \times 10^3 \leq P \leq 1.5522 \times 10^6$ [Pa] $0.9367 \leq P \leq 15.522$ [bar]
8	ALMPT(P,T)	ALMPT: Thermal Conductivity at Ordinary Pressure [W/(m·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	P=Dummy $144 \leq T \leq 278$ [K] $-129.15 \leq T \leq 4.85$ [°C]
9	ALMTD(T)	ALMTD: Thermal Conductivity of Saturated Liquid [W/(m·K)] T*: Temperature [K], [°C]	$140 \leq T \leq 210$ [K] $-133.15 \leq T \leq -63.15$ [°C]
10	ALMTDD(T)	ALMTDD: Thermal Conductivity of Saturated Vapor [W/(m·K)] T*: Temperature [K], [°C]	$144 \leq T \leq 200$ [K] $-129.15 \leq T \leq -73.15$ [°C]
11	AMUPD(P)		
12	AMUPDD(P)		
13	AMUPT(P,T)		
14	AMUTD(T)		
15	AMUTDD(T)		
92	BPPT(P,T)		
90	BSPT(P,T)		
91	BTPT(P,T)		
93	BVPT(P,T)		
16	CPPD(P)	CPPD: Isobaric Specific Heat of Saturated Liquid [J/(kg·K)] P*: Pressure [Pa], [bar]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar]
17	CPPDD(P)	CPPDD: Isobaric Specific Heat of Saturated Vapor [J/(kg·K)] P*: Pressure [Pa], [bar]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar]
18	CPPT(P,T)	CPPT: Isobaric Specific Heat [J/(kg·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$600 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $110 \leq T \leq 620$ [K] $6 \leq P \leq 500$ [bar] $-163.15 \leq T \leq 346.85$ [°C]
19	CPTD(T)	CPTD: Isobaric Specific Heat of Saturated Liquid [J/(kg·K)] T*: Temperature [K], [°C]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C]

Table II-2.31-1 FC-14(R-14) Function (cont'd)

No.	Name of Function	Function and Argument(s)	Range of Argument(s)
20	CPTDD(T)	CPTDD: Isobaric Specific Heat of Saturated Vapor [J/(kg·K)] T*: Temperature [K], [°C]	105 ≤ T ≤ 227.51 [K] -168.15 ≤ T ≤ -45.64 [°C]
21	CRP('A')	CRP: Critical Constants H: 'A'='H': 0.3266 × 10 ⁶ [J/kg] Specific Enthalpy P*: 'A'='P': 3.750 × 10 ⁶ [Pa], 37.50 [bar] Pressure S: 'A'='S': 1.678 × 10 ³ [J/(kg·K)] Specific Entropy T*: 'A'='T': 227.51 [K], -45.64 [°C] Temperature V: 'A'='V': 1.598 × 10 ⁻³ [m ³ /kg] Specific Volume	one of 'H', 'P', 'S', 'T' and 'V'
7A	CVPD(P)		
76	CVPDD(P)	CVPDD: Isochoric Specific Heat of Saturated Vapor [J/(kg·K)] P*: Pressure [Pa], [bar]	1.69 × 10 ³ ≤ P ≤ 3.75 × 10 ⁶ [Pa] 0.0169 ≤ P ≤ 37.5 [bar]
77	CVPT(P,T)	CVPT: Isochoric Specific Heat [J/(kg·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	600 × 10 ³ ≤ P ≤ 50 × 10 ⁶ [Pa] 110 ≤ T ≤ 620 [K] 6 ≤ P ≤ 500 [bar] -163.15 ≤ T ≤ 346.85 [°C]
7B	CVTD(T)		
78	CVTDD(T)	CVTDD: Isochoric Specific Heat of Saturated Vapor [J/(kg·K)] T*: Temperature [K], [°C]	105 ≤ T ≤ 227.51 [K] -168.15 ≤ T ≤ -45.64 [°C]
2A	EPSPD(P)		
2B	EPSPDD(P)		
22	EPSPT(P,T)		
2C	EPSTD(T)		
2D	EPSTDD(T)		
89	FC('A')	FC: Fundamental Constants M: 'A'='M': 88.010 Relative Molecular Mass R: 'A'='R': 94.472 [J/(kg·K)] Gas Constant	one of 'M' and 'R'
9A	GAMPD(P)		
96	GAMPDD(P)		
95	GAMPT(P,T)		
9B	GAMTD(T)		
97	GAMTDD(T)		
23	HPD(P)	HPD: Specific Enthalpy of Saturated Liquid [J/kg] P*: Pressure [Pa], [bar]	1.69 × 10 ³ ≤ P ≤ 3.75 × 10 ⁶ [Pa] 0.0169 ≤ P ≤ 37.5 [bar]
24	HPDD(P)	HPDD: Specific Enthalpy of Saturated Vapor [J/kg] P*: Pressure [Pa], [bar]	1.69 × 10 ³ ≤ P ≤ 3.75 × 10 ⁶ [Pa] 0.0169 ≤ P ≤ 37.5 [bar]
71	HPS(P,S)	HPS: Specific Enthalpy [J/kg] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)]	600 × 10 ³ ≤ P ≤ 50 × 10 ⁶ [Pa] SPT(P,110K) ≤ S ≤ SPT(P,620K) [J/(kg·K)] 6 ≤ P ≤ 500 [bar] SPT(P,-163.15°C) ≤ S ≤ SPT(P,346.85°C) [J/(kg·K)]
25	HPT(P,T)	HPT: Specific Enthalpy [J/kg] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	600 × 10 ³ ≤ P ≤ 50 × 10 ⁶ [Pa] 110 ≤ T ≤ 620 [K] 6 ≤ P ≤ 500 [bar] -163.15 ≤ T ≤ 346.85 [°C]
26	HPX(P,X)	HPX: Specific Enthalpy of Mixture [J/kg] P*: Pressure [Pa], [bar] X: Dryness Fraction [-]	1.69 × 10 ³ ≤ P ≤ 3.75 × 10 ⁶ [Pa] 0.0169 ≤ P ≤ 37.5 [bar] 0 ≤ X ≤ 1.0 [-]
27	HTD(T)	HTD: Specific Enthalpy of Saturated Liquid [J/kg] T*: Temperature [K], [°C]	105 ≤ T ≤ 227.51 [K] -168.15 ≤ T ≤ -45.64 [°C]
28	HTDD(T)	HTDD: Specific Enthalpy of Saturated Vapor [J/kg] T*: Temperature [K], [°C]	105 ≤ T ≤ 227.51 [K] -168.15 ≤ T ≤ -45.64 [°C]

Table II-2.31-1 FC-14(R-14) Function (cont'd)

No.	Name of Function	Function and Argument(s)	Range of Argument(s)
29	HTX(T,X)	HTX: Specific Enthalpy of Mixture [J/kg] T*: Temperature [K], [°C] X: Dryness Fraction [-]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C] $0 \leq X \leq 1.0$ [-]
84	IDENTF('A')	IDENTF: CHARACTER TYPE FUNCTION for Identification of Substance (Length 20) C: 'A'='C': 'CF4' Molecular Formula S: 'A'='S': 'FC-14(R-14)' Name of Substance V: 'A'='V': '10.1' Version Number	one of 'C', 'S' and 'V'
66	PLDT(T)		
68	PMLT(T)		
85	PRPD(P)		
86	PRPDD(P)		
81	PRPT(P,T)		
87	PRTD(T)		
88	PRTDD(T)		
99	PSBT(T)		
30	PST(T)	PST*: Saturation Pressure [Pa], [bar] T*: Temperature [K], [°C]	$110 \leq T \leq 227.51$ [K] $-163.15 \leq T \leq -45.64$ [°C]
72	PSTD(T)		
73	PSTDD(T)		
31	SIGP(P)	SIGP: Surface Tension [N/m] P*: Pressure [Pa], [bar]	$PST(110K) < P \leq 3.75 \times 10^6$ [Pa] ($\sim 1.55 \times 10^6$) $PST(-163.15 \text{ } ^\circ\text{C}) \leq P \leq 37.5$ [bar] (~ 15.5)
32	SIGT(T)	SIGT: Surface Tension [N/m] T*: Temperature [K], [°C]	$110 \leq T \leq 227.51$ [K] $-163.15 \leq T \leq -45.64$ [°C]
33	SPD(P)	SPD: Specific Entropy of Saturated Liquid [J/(kg·K)] P*: Pressure [Pa], [bar]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar]
34	SPDD(P)	SPDD: Specific Entropy of Saturated Vapor [J/(kg·K)] P*: Pressure [Pa], [bar]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar]
35	SPT(P,T)	SPT: Specific Entropy [J/(kg·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$600 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $110 \leq T \leq 620$ [K] $6 \leq P \leq 500$ [bar] $-163.15 \leq T \leq 346.85$ [°C]
36	SPX(P,X)	SPX: Specific Entropy of Mixture [J/(kg·K)] P*: Pressure [Pa], [bar] X: Dryness Fraction [-]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar] $0 \leq X \leq 1.0$ [-]
37	STD(T)	STD: Specific Entropy of Saturated Liquid [J/(kg·K)] T*: Temperature [K], [°C]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C]
38	STDD(T)	STDD: Specific Entropy of Saturated Vapor [J/(kg·K)] T*: Temperature [K], [°C]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C]
39	STX(T,X)	STX: Specific Entropy of Mixture [J/(kg·K)] T*: Temperature [K], [°C] X: Dryness Fraction [-]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C] $0 \leq X \leq 1.0$ [-]
67	TLDP(P)		
69	TMLP(P)		
64	TPH(P,H)	TPH*: Temperature [K], [°C] P*: Pressure [Pa], [bar] H: Specific Enthalpy [J/kg]	$600 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $HPT(P,110K) \leq H \leq$ $HPT(P,620K)$ [J/kg] $6 \leq P \leq 500$ [bar] $HPT(P,-163.15 \text{ } ^\circ\text{C}) \leq H \leq$ $HPT(P,346.85 \text{ } ^\circ\text{C})$ [J/kg]

Table II-2.31-1 FC-14(R-14) Function (cont'd)

No.	Name of Function	Function and Argument(s)	Range of Argument(s)
6H	TPH2(P,H)		
65	TPS(P,S)	TPS*: Temperature [K], [°C] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)]	$600 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $SPT(P, 110K) \leq S \leq$ $SPT(P, 620K)$ [J/(kg·K)] $6 \leq P \leq 500$ [bar] $SPT(P, -163.15^\circ C) \leq S \leq$ $SPT(P, 346.85^\circ C)$ [J/(kg·K)]
6S	TPS2(P,S)		
98	TPSEUP(P)		
70	TPV(P,V)	TPV*: Temperature [K], [°C] P*: Pressure [Pa], [bar] V: Specific Volume [m ³ /kg]	$600 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $VPT(P, 110K) \leq V \leq$ $VPT(P, 620K)$ [m ³ /kg] $6 \leq P \leq 500$ [bar] $VPT(P, -163.15^\circ C) \leq V \leq$ $VPT(P, 346.85^\circ C)$ [m ³ /kg]
41	TRPL('A')		
100	TSBP(P)		
40	TSP(P)	TSP*: Saturation Temperature [K], [°C] P*: Pressure [Pa], [bar]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar]
74	TSPD(P)		
75	TSPDD(P)		
42	UPD(P)	UPD: Specific Internal Energy of Saturated Liquid [J/kg] P*: Pressure [Pa], [bar]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar]
43	UPDD(P)	UPDD: Specific Internal Energy of Saturated Vapor [J/kg] P*: Pressure [Pa], [bar]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar]
79	UPS(P,S)	UPS: Specific Internal Energy [J/kg] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)]	$600 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $SPT(P, 110K) \leq S \leq$ $SPT(P, 620K)$ [J/(kg·K)] $6 \leq P \leq 500$ [bar] $SPT(P, -163.15^\circ C) \leq S \leq$ $SPT(P, 346.85^\circ C)$ [J/(kg·K)]
44	UPT(P,T)	UPT: Specific Internal Energy [J/kg] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$600 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $110 \leq T \leq 620$ [K] $6 \leq P \leq 500$ [bar] $-163.15 \leq T \leq 346.85$ [°C]
45	UPX(P,X)	UPX: Specific Internal Energy of Mixture [J/kg] P*: Pressure [Pa], [bar] X: Dryness Fraction [-]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar] $0 \leq X \leq 1.0$ [-]
46	UTD(T)	UTD: Specific Internal Energy of Saturated Liquid [J/kg] T*: Temperature [K], [°C]	$110 \leq T \leq 227.51$ [K] $-163.15 \leq T \leq -45.64$ [°C]
47	UTDD(T)	UTDD: Specific Internal Energy of Saturated Vapor [J/kg] T*: Temperature [K], [°C]	$110 \leq T \leq 227.51$ [K] $-163.15 \leq T \leq -45.64$ [°C]
48	UTX(T,X)	UTX: Specific Internal Energy of Mixture [J/kg] T*: Temperature [K], [°C] X: Dryness Fraction [-]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C] $0 \leq X \leq 1.0$ [-]

Table II-2.31-1 FC-14(R-14) Function (cont'd)

No.	Name of Function	Function and Argument(s)	Range of Argument(s)
49	VPD(P)	VPD: Specific Volume of Saturated Liquid [m ³ /kg] P*: Pressure [Pa], [bar]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar]
50	VPDD(P)	VPDD: Specific Volume of Saturated Vapor [m ³ /kg] P*: Pressure [Pa], [bar]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar]
80	VPS(P,S)	VPS: Specific Volume [m ³ /kg] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)]	$600 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] SPT(P,110K) ≤ S ≤ SPT(P,620K) [J/(kg·K)] $6 \leq P \leq 500$ [bar] SPT(P, -163.15°C) ≤ S ≤ SPT(P,346.85°C) [J/(kg·K)]
51	VPT(P,T)	VPT: Specific Volume [m ³ /kg] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$600 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $110 \leq T \leq 620$ [K] $6 \leq P \leq 500$ [bar] $-163.15 \leq T \leq 346.85$ [°C]
52	VPX(P,X)	VPX: Specific Volume of Mixture [m ³ /kg] P*: Pressure [Pa], [bar] X: Dryness Fraction [-]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar] $0 \leq X \leq 1.0$ [-]
53	VTD(T)	VTD: Specific Volume of Saturated Liquid [m ³ /kg] T*: Temperature [K], [°C]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C]
54	VTDD(T)	VTDD: Specific Volume of Saturated Vapor [m ³ /kg] T*: Temperature [K], [°C]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C]
55	VTX(T,X)	VTX: Specific Volume of Mixture [m ³ /kg] T*: Temperature [K], [°C] X: Dryness Fraction [-]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C] $0 \leq X \leq 1.0$ [-]
8E	WPD(P)		
8F	WPDD(P)		
83	WPT(P,T)	WPT: Velocity of Sound [m/s] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$600 \times 10^3 \leq P \leq 50 \times 10^6$ [Pa] $110 \leq T \leq 620$ [K] $6 \leq P \leq 500$ [bar] $-163.15 \leq T \leq 346.85$ [°C]
8G	WTD(T)		
8H	WTDD(T)		
56	XPH(P,H)	XPH: Dryness Fraction [-] P*: Pressure [Pa], [bar] H: Specific Enthalpy of Mixture [J/kg]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar] HPD(P) ≤ H ≤ HPDD(P) [J/kg]
57	XPS(P,S)	XPS: Dryness Fraction [-] P*: Pressure [Pa], [bar] S: Specific Entropy of Mixture [J/(kg·K)]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar] SPD(P) ≤ S ≤ SPDD(P) [J/(kg·K)]
58	XPU(P,U)	XPU: Dryness Fraction [-] P*: Pressure [Pa], [bar] U: Specific Internal Energy of Mixture [J/kg]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar] UPD(P) ≤ U ≤ UPDD(P) [J/kg]
59	XPV(P,V)	XPV: Dryness Fraction [-] P*: Pressure [Pa], [bar] V: Specific Volume of Mixture [m ³ /kg]	$1.69 \times 10^3 \leq P \leq 3.75 \times 10^6$ [Pa] $0.0169 \leq P \leq 37.5$ [bar] VPD(P) ≤ V ≤ VPDD(P) [m ³ /kg]
60	XTH(T,H)	XTH: Dryness Fraction [-] T*: Temperature [K], [°C] H: Specific Enthalpy of Mixture [J/kg]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C] HTD(T) ≤ H ≤ HTDD(T) [J/kg]
61	XTS(T,S)	XTS: Dryness Fraction [-] T*: Temperature [K], [°C] S: Specific Entropy of Mixture [J/(kg·K)]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C] STD(T) ≤ S ≤ STDD(T) [J/(kg·K)]
62	XTU(T,U)	XTU: Dryness Fraction [-] T*: Temperature [K], [°C] U: Specific Internal Energy of Mixture [J/kg]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C] UTD(T) ≤ U ≤ UTDD(T) [J/kg]
63	XTV(T,V)	XTV: Dryness Fraction [-] T*: Temperature [K], [°C] V: Specific Volume of Mixture [m ³ /kg]	$105 \leq T \leq 227.51$ [K] $-168.15 \leq T \leq -45.64$ [°C] VTD(T) ≤ V ≤ VTDD(T) [m ³ /kg]