

2.44 HFC-23(R23)

All equations for HFC-23(R23) are based on the Table from Thermophysical properties of refrigerants by Platzer *et al.*[1].

2.44.1 Temperature Scale

International practical temperature scale 1968 (IPTS-1968)

2.44.2 The Names of Substance, Library File and Single Shot Program

Name of Substance:	HFC-23, R23, Refrigerant 23, Freon 23, Fluoroform, Trifluoromethane
Library File for UNIX:	libjr23.a
Library File for DOS,Windows95/NT:	JR23.LIB
Single Shot Program for UNIX:	r23-ss
Single Shot Program for DOS,Windows95/NT:	R23-SS.EXE

2.44.3 Important Constants and Others

Molecular Formula:	CHF ₃
Relative Molecular Mass:	70.019
Gas Constant:	118.75 J/(kg·K)

Critical Constants:

Critical Pressure:	4.8162×10 ⁶ Pa (48.162 bar)
Critical Temperature:	299.01 K (25.86 °C)
Critical Specific Volume:	1.9231×10 ⁻³ m ³ /kg

Reference State:

At 0°C, 1.0000 kJ/(kg·K) and 200.00 kJ/kg are assigned to the specific entropy and the specific enthalpy of saturated liquid, respectively.

2.44.4 Formula

Equation of State:

The Bender equation of state (II-3-1) in reference [1], which is in a function from of $Z = Z(\rho, T)$. Here Z =compressibility, ρ =density and T =temperature.

Vapor Pressure:

Equation (20) in reference [1].

Properties at Vapor-Liquid Equilibrium:

saturated state: The Bender equation of state is utilized to obtaining saturated specific volume by the aid of Maxwell's criterion according to the author's recommendation. The Bender equation of state shows unreasonable behavior near the critical point. This temperature range is evaluated by $T_c \pm 1$ K. Therefore, in the temperature range and above the critical pressure, the values of u , h and s would include some uncertainty. Also, in the ranges of $p_{sat}(T_c - 1K) < p < p_{sat}(T_c + 1K)$ and $v'(T_c - 1K) < v < v''(T_c - 1K)$, the calculated values of p , v , T , c_p , c_v , isentropic exponent, Laplace coefficient, Prandtl number, velocity of sound and dryness fraction of wet vapor would have some uncertainty. Equations (2), (3), and (5) for specific enthalpy, specific entropy and isobaric specific heat, respectively. However, the sign of the last integration term in Equation (2) for u

$$u(T, \rho) = h_0 - RT_0 + \int_{T_0}^T (c_p^0 - R)dT + \int_0^\rho \left[T \left(\frac{\partial p}{\partial T} \right)_\rho - p \right] \frac{d\rho}{\rho^2}$$

has been corrected to

$$u(T, \rho) = h_0 - RT_0 + \int_{T_0}^T (c_p^0 - R)dT - \int_0^\rho \left[T \left(\frac{\partial p}{\partial T} \right)_\rho - p \right] \frac{d\rho}{\rho^2}.$$

Transport Properties:

Thermal conductivity and viscosity from reference [2].

The Other Properties:

Equation (3) in reference [3] for surface tension.

References

- [1] B.Platzer, A.Polt and G.Maurer, Thermophysical Properties of Refrigerants (1990), Springer-Verlag
- [2] Thermophysical Properties of Refrigerants(1976), 37 ASHRAE
- [3] K.Watanabe and M.Okada, Int. J. Thermophysics, 2-2(1981), p.163

Table II-2.44-1 HFC-23(R-23) Function

No.	Name of Function	Function and Argument(s)	Range of Argument(s)
1	AIPPT(P,T)		
94	AJTPT(P,T)		
8A	AKPD(P)		
8B	AKPDD(P)		
82	AKPT(P,T)	AKPT: Isentropic Exponent [-] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $200 \leq T \leq 470$ [K] $1.0 \leq P \leq 580$ [bar] $-73.15 \leq T \leq 196.85$ [°C]
8C	AKTD(T)		
8D	AKTDD(T)		
2	ALAPP(P)	ALAPP: Laplace Coefficient [m] P*: Pressure [Pa], [bar]	$22.845 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.22845 \leq P \leq 48.162$ [bar]
3	ALAPT(T)	ALAPT: Laplace Coefficient [m] T*: Temperature [K], [°C]	$210 \leq T \leq 299.01$ [K] $-63.15 \leq T \leq 25.86$ [°C]
4	ALHP(P)	ALHP: Latent Heat of Vaporization [J/kg] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
5	ALHT(T)	ALHT: Latent Heat of Vaporization [J/kg] T*: Temperature [K], [°C]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
6	ALMPD(P)	ALMPD: Thermal Conductivity of Saturated Liquid [W/(m·K)] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 2.3033 \times 10^6$ [Pa] $0.0257 \leq P \leq 23.033$ [bar]
7	ALMPDD(P)	ALMPDD: Thermal Conductivity of Saturated Vapor [W/(m·K)] T*: Temperature [K], [°C]	$70.25 \times 10^3 \leq P \leq 0.7622 \times 10^6$ [Pa] $0.7025 \leq P \leq 7.622$ [bar]
8	ALMPT(P,T)	ALMPT: Thermal Conductivity at Ordinary Pressure [W/(m·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	P=Dummy $189 \leq T \leq 478$ [K] $-84.15 \leq T \leq 204.85$ [°C]
9	ALMTD(T)	ALMTD: Thermal Conductivity of Saturated Liquid [W/(m·K)] T*: Temperature [K], [°C]	$122 \leq T \leq 270$ [K] $-151.15 \leq T \leq -3.15$ [°C]
10	ALMTDD(T)	ALMTDD: Thermal Conductivity of Saturated Vapor [W/(m·K)] T*: Temperature [K], [°C]	$185 \leq T \leq 235$ [K] $-88.15 \leq T \leq -38.15$ [°C]
11	AMUPD(P)	AMUPD: Coefficient of Viscosity of Saturated Liquid [Pa·s] P*: Pressure [Pa], [bar]	$16.56 \times 10^3 \leq P \leq 1.7313 \times 10^6$ [Pa] $0.1656 \leq P \leq 17.313$ [bar]
12	AMUPDD(P)	AMUPDD: Coefficient of Viscosity of Saturated Vapor [Pa·s] P*: Pressure [Pa], [bar]	$0.56626 \times 10^6 \leq P \leq 4.8162 \times 10^6$ [Pa] $5.6626 \leq P \leq 48.162$ [bar]
13	AMUPT(P,T)		
14	AMUTD(T)	AMUTD: Coefficient of Viscosity of Saturated Liquid [Pa·s] T*: Temperature [K], [°C]	$200 \leq T \leq 260$ [K] $-73.15 \leq T \leq -13.15$ [°C]
15	AMUTDD(T)	AMUTDD: Coefficient of Viscosity of Saturated Vapor [Pa·s] T*: Temperature [K], [°C]	$200 \leq T \leq 290$ [K] $-73.15 \leq T \leq 16.85$ [°C]
92	BPPT(P,T)		
90	BSPT(P,T)		
91	BTPT(P,T)		
93	BVPT(P,T)		
16	CPPD(P)	CPPD: Isobaric Specific Heat of Saturated Liquid [J/(kg·K)] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]

Table II-2.44-1 HFC-23(R-23) Function (cont'd)

No.	Name of Function	Function and Argument(s)	Range of Argument(s)
17	CPPDD(P)	CPPDD: Isobaric Specific Heat of Saturated Vapor [J/(kg·K)] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
18	CPPT(P,T)	CPPT: Isobaric Specific Heat [J/(kg·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $200 \leq T \leq 470$ [K] $1.0 \leq P \leq 580$ [bar] $-73.15 \leq T \leq 196.85$ [°C]
19	CPTD(T)	CPTD: Isobaric Specific Heat of Saturated Liquid [J/(kg·K)] T*: Temperature [K], [°C]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
20	CPTDD(T)	CPTDD: Isobaric Specific Heat of Saturated Vapor [J/(kg·K)] T*: Temperature [K], [°C]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
21	CRP('A')	CRP: Critical Constants H: 'A'='H': 0.2806×10^6 [J/kg] Specific Enthalpy P*: 'A'='P': 4.8162×10^6 [Pa], 48.162 [bar] Pressure S: 'A'='S': 1.272×10^3 [J/(kg·K)] Specific Entropy T*: 'A'='T': 299.01 [K], 25.86 [°C] Temperature V: 'A'='V': 1.923×10^{-3} [m ³ /kg] Specific Volume	one of 'H', 'P', 'S', 'T' and 'V'
7A	CVPD(P)		
76	CVPDD(P)	CVPDD: Isochoric Specific Heat of Saturated Vapor [J/(kg·K)] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
77	CVPT(P,T)	CVPT: Isochoric Specific Heat [J/(kg·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $200 \leq T \leq 470$ [K] $1.0 \leq P \leq 580$ [bar] $-73.15 \leq T \leq 196.85$ [°C]
7B	CVTD(T)		
78	CVTDD(T)	CVTDD: Isochoric Specific Heat of Saturated Vapor [J/(kg·K)] T*: Temperature [K], [°C]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
2A	EPSPD(P)		
2B	EPSPDD(P)		
22	EPSPPT(P,T)		
2C	EPSTD(T)		
2D	EPSTDD(T)		
89	FC('A')	FC: Fundamental Constants M: 'A'='M': 70.019 Relative Molecular Mass R: 'A'='R': 118.75 [J/(kg·K)] Gas Constant	one of 'M' and 'R'
9A	GAMPD(P)		
96	GAMPDD(P)		
95	GAMPPT(P,T)		
9B	GAMTD(T)		
97	GAMTDD(T)		
23	HPD(P)	HPD: Specific Enthalpy of Saturated Liquid [J/kg] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
24	HPDD(P)	HPDD: Specific Enthalpy of Saturated Vapor [J/kg] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
71	HPS(P,S)	HPS: Specific Enthalpy [J/kg] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] SPT(P,200K) $\leq S \leq$ SPT(P,470K) [J/(kg·K)] $1.0 \leq P \leq 580$ [bar] SPT(P, -73.15°C) $\leq S \leq$ SPT(P,196.85°C) [J/(kg·K)]

Table II-2.44-1 HFC-23(R-23) Function (cont'd)

No.	Name of Function	Function and Argument(s)	Range of Argument(s)
25	HPT(P,T)	HPT: Specific Enthalpy [J/kg] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $200 \leq T \leq 470$ [K] $1.0 \leq P \leq 580$ [bar] $-73.15 \leq T \leq 196.85$ [°C]
26	HPX(P,X)	HPX: Specific Enthalpy of Mixture [J/kg] P*: Pressure [Pa], [bar] X: Dryness Fraction [-]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar] $0 \leq X \leq 1.0$ [-]
27	HTD(T)	HTD: Specific Enthalpy of Saturated Liquid [J/kg] T*: Temperature [K], [°C]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
28	HTDD(T)	HTDD: Specific Enthalpy of Saturated Vapor [J/kg] T*: Temperature [K], [°C]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
29	HTX(T,X)	HTX: Specific Enthalpy of Mixture [J/kg] T*: Temperature [K], [°C] X: Dryness Fraction [-]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C] $0 \leq X \leq 1.0$ [-]
84	IDENTF('A')	IDENTF: CHARACTER TYPE FUNCTION for Identification of Substance (Length 20) C: 'A'='C': 'CHF3' Molecular Formula S: 'A'='S': 'HFC-23(R-23)' Name of Substance V: 'A'='V': '10.1' Version Number	one of 'C', 'S' and 'V'
66	PLDT(T)		
68	PMLT(T)		
85	PRPD(P)	PRPD: Prandtl Number of Saturated Liquid [-] P*: Pressure [Pa], [bar]	$16.56 \times 10^3 \leq P \leq 1.7313 \times 10^6$ [Pa] $1.656 \leq P \leq 17.313$ [bar]
86	PRPDD(P)	PRPDD: Prandtl Number of Saturated Vapor [-] P*: Pressure [Pa], [bar]	$70.25 \times 10^3 \leq P \leq 0.7622 \times 10^6$ [Pa] $0.7025 \leq P \leq 7.622$ [bar]
81	PRPT(P,T)		
87	PRTD(T)	PRTD: Prandtl Number of Saturated Liquid [-] T*: Temperature [K], [°C]	$200 \leq T \leq 260$ [K] $-73.15 \leq T \leq -13.15$ [°C]
88	PRTDD(T)	PRTDD: Prandtl Number of Saturated Vapor [-] T*: Temperature [K], [°C]	$185 \leq T \leq 235$ [K] $-88.15 \leq T \leq -38.15$ [°C]
99	PSBT(T)		
30	PST(T)	PST*: Saturation Pressure [Pa], [bar] T*: Temperature [K], [°C]	$200 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
72	PSTD(T)		
73	PSTDD(T)		
31	SIGP(P)	SIGP: Surface Tension [N/m] P*: Pressure [Pa], [bar]	$PST(200K) \leq P \leq 4.8162 \times 10^6$ [Pa] ($\sim 166 \times 10^3$) $PST(-73.15 \text{ } ^\circ\text{C}) \leq P \leq 48.162$ [bar] (~ 1.66)
32	SIGT(T)	SIGT: Surface Tension [N/m] T*: Temperature [K], [°C]	$200 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
33	SPD(P)	SPD: Specific Entropy of Saturated Liquid [J/(kg·K)] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
34	SPDD(P)	SPDD: Specific Entropy of Saturated Vapor [J/(kg·K)] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
35	SPT(P,T)	SPT: Specific Entropy [J/(kg·K)] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $200 \leq T \leq 470$ [K] $1.0 \leq P \leq 580$ [bar] $-73.15 \leq T \leq 196.85$ [°C]
36	SPX(P,X)	SPX: Specific Entropy of Mixture [J/(kg·K)] P*: Pressure [Pa], [bar] X: Dryness Fraction [-]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar] $0 \leq X \leq 1.0$ [-]
37	STD(T)	STD: Specific Entropy of Saturated Liquid [J/(kg·K)] T*: Temperature [K], [°C]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]

Table II-2.44-1 HFC-23(R-23) Function (cont'd)

No.	Name of Function	Function and Argument(s)	Range of Argument(s)
38	STDD(T)	STDD: Specific Entropy of Saturated Vapor [J/(kg·K)] T*: Temperature [K], [°C]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
39	STX(T,X)	STX: Specific Entropy of Mixture [J/(kg·K)] T*: Temperature [K], [°C] X: Dryness Fraction [-]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C] $0 \leq X \leq 1.0$ [-]
67	TLDP(P)		
69	TMLP(P)		
64	TPH(P,H)	TPH*: Temperature [K], [°C] P*: Pressure [Pa], [bar] H: Specific Enthalpy [J/kg]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $HPT(P, 200K) \leq H \leq$ $HPT(P, 470K)$ [J/kg] $1.0 \leq P \leq 580$ [bar] $HPT(P, -73.15^\circ C) \leq H \leq$ $HPT(P, 196.85^\circ C)$ [J/kg]
6H	TPH2(P,H)		
65	TPS(P,S)	TPS*: Temperature [K], [°C] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $SPT(P, 200K) \leq S \leq$ $SPT(P, 470K)$ [J/(kg·K)] $1.0 \leq P \leq 580$ [bar] $SPT(P, -73.15^\circ C) \leq S \leq$ $SPT(P, 196.85^\circ C)$ [J/(kg·K)]
6S	TPS2(P,S)		
98	TPSEUP(P)		
70	TPV(P,V)	TPV*: Temperature [K], [°C] P*: Pressure [Pa], [bar] V: Specific Volume [m ³ /kg]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $VPT(P, 200K) \leq V \leq$ $VPT(P, 470K)$ [m ³ /kg] $1.0 \leq P \leq 580$ [bar] $VPT(P, -73.15^\circ C) \leq V \leq$ $VPT(P, 196.85^\circ C)$ [m ³ /kg]
41	TRPL('A')		
100	TSBP(P)		
40	TSP(P)	TSP*: Saturation Temperature [K], [°C] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
74	TSPD(P)		
75	TSPDD(P)		
42	UPD(P)	UPD: Specific Internal Energy of Saturated Liquid [J/kg] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
43	UPDD(P)	UPDD: Specific Internal Energy of Saturated Vapor [J/kg] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
79	UPS(P,S)	UPS: Specific Internal Energy [J/kg] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $SPT(P, 200K) \leq S \leq$ $SPT(P, 470K)$ [J/(kg·K)] $1.0 \leq P \leq 580$ [bar] $SPT(P, -73.15^\circ C) \leq S \leq$ $SPT(P, 196.85^\circ C)$ [J/(kg·K)]

Table II-2.44-1 HFC-23(R-23) Function (cont'd)

No.	Name of Function	Function and Argument(s)	Range of Argument(s)
44	UPT(P,T)	UPT: Specific Internal Energy [J/kg] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $200 \leq T \leq 470$ [K] $1.0 \leq P \leq 580$ [bar] $-73.15 \leq T \leq 196.85$ [°C]
45	UPX(P,X)	UPX: Specific Internal Energy of Mixture [J/kg] P*: Pressure [Pa], [bar] X: Dryness Fraction [-]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar] $0 \leq X \leq 1.0$ [-]
46	UTD(T)	UTD: Specific Internal Energy of Saturated Liquid [J/kg] T*: Temperature [K], [°C]	$200 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
47	UTDD(T)	UTDD: Specific Internal Energy of Saturated Vapor [J/kg] T*: Temperature [K], [°C]	$200 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
48	UTX(T,X)	UTX: Specific Internal Energy of Mixture [J/kg] T*: Temperature [K], [°C] X: Dryness Fraction [-]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C] $0 \leq X \leq 1.0$ [-]
49	VPD(P)	VPD: Specific Volume of Saturated Liquid [m ³ /kg] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
50	VPDD(P)	VPDD: Specific Volume of Saturated Vapor [m ³ /kg] P*: Pressure [Pa], [bar]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar]
80	VPS(P,S)	VPS: Specific Volume [m ³ /kg] P*: Pressure [Pa], [bar] S: Specific Entropy [J/(kg·K)]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] SPT(P,200K) ≤ S ≤ SPT(P,470K) [J/(kg·K)] $1.0 \leq P \leq 580$ [bar] SPT(P, -73.15°C) ≤ S ≤ SPT(P,196.85°C) [J/(kg·K)]
51	VPT(P,T)	VPT: Specific Volume [m ³ /kg] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $200 \leq T \leq 470$ [K] $1.0 \leq P \leq 580$ [bar] $-73.15 \leq T \leq 196.85$ [°C]
52	VPX(P,X)	VPX: Specific Volume of Mixture [m ³ /kg] P*: Pressure [Pa], [bar] X: Dryness Fraction [-]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar] $0 \leq X \leq 1.0$ [-]
53	VTD(T)	VTD: Specific Volume of Saturated Liquid [m ³ /kg] T*: Temperature [K], [°C]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
54	VTDD(T)	VTDD: Specific Volume of Saturated Vapor [m ³ /kg] T*: Temperature [K], [°C]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C]
55	VTX(T,X)	VTX: Specific Volume of Mixture [m ³ /kg] T*: Temperature [K], [°C] X: Dryness Fraction [-]	$145 \leq T \leq 299.01$ [K] $-128.15 \leq T \leq 25.86$ [°C] $0 \leq X \leq 1.0$ [-]
8E	WPD(P)		
8F	WPDD(P)		
83	WPT(P,T)	WPT: Velocity of Sound [m/s] P*: Pressure [Pa], [bar] T*: Temperature [K], [°C]	$100 \times 10^3 \leq P \leq 58 \times 10^6$ [Pa] $200 \leq T \leq 470$ [K] $1.0 \leq P \leq 580$ [bar] $-73.15 \leq T \leq 196.85$ [°C]
8G	WTD(T)		
8H	WTDD(T)		
56	XPH(P,H)	XPH: Dryness Fraction [-] P*: Pressure [Pa], [bar] H: Specific Enthalpy of Mixture [J/kg]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar] HPD(P) ≤ H ≤ HPDD(P) [J/kg]
57	XPS(P,S)	XPS: Dryness Fraction [-] P*: Pressure [Pa], [bar] S: Specific Entropy of Mixture [J/(kg·K)]	$2.57 \times 10^3 \leq P \leq 4.8162 \times 10^6$ [Pa] $0.0257 \leq P \leq 48.162$ [bar] SPD(P) ≤ S ≤ SPDD(P) [J/(kg·K)]

Table II-2.44-1 HFC-23(R-23) Function (cont'd)

No.	Name of Function	Function and Argument(s)	Range of Argument(s)
58	XPU(P,U)	XPU: Dryness Fraction [-] P*: Pressure [Pa], [bar] U: Specific Internal Energy of Mixture [J/kg]	$2.57 \times 10^3 \leq P < 4.8162 \times 10^6$ [Pa] $0.0257 \leq P < 48.162$ [bar] $UPD(P) \leq U \leq UPDD(P)$ [J/kg]
59	XPV(P,V)	XPV: Dryness Fraction [-] P*: Pressure [Pa], [bar] V: Specific Volume of Mixture [m ³ /kg]	$2.57 \times 10^3 \leq P < 4.8162 \times 10^6$ [Pa] $0.0257 \leq P < 48.162$ [bar] $VPD(P) \leq V \leq VPDD(P)$ [m ³ /kg]
60	XTH(T,H)	XTH: Dryness Fraction [-] T*: Temperature [K], [°C] H: Specific Enthalpy of Mixture [J/kg]	$145 \leq T < 299.01$ [K] $-128.15 \leq T < 25.86$ [°C] $HTD(T) \leq H \leq HTDD(T)$ [J/kg]
61	XTS(T,S)	XTS: Dryness Fraction [-] T*: Temperature [K], [°C] S: Specific Entropy of Mixture [J/(kg·K)]	$145 \leq T < 299.01$ [K] $-128.15 \leq T < 25.86$ [°C] $STD(T) \leq S \leq STDD(T)$ [J/(kg·K)]
62	XTU(T,U)	XTU: Dryness Fraction [-] T*: Temperature [K], [°C] U: Specific Internal Energy of Mixture [J/kg]	$145 \leq T < 299.01$ [K] $-128.15 \leq T < 25.86$ [°C] $UTD(T) \leq U \leq UTDD(T)$ [J/kg]
63	XTV(T,V)	XTV: Dryness Fraction [-] T*: Temperature [K], [°C] V: Specific Volume of Mixture [m ³ /kg]	$145 \leq T < 299.01$ [K] $-128.15 \leq T < 25.86$ [°C] $VTD(T) \leq V \leq VTDD(T)$ [m ³ /kg]